
PRE-FILLED IP68

LOW VOLTAGE

Ray









Electrical performance: • CEI EN 50393 as applicable • Class 2 in accordance with CEI 64-8. Gel: UL 94-HB CNUs ٥ Ω≣ Working temperature: 90° Gel operating temperature: J -60°C / +200°C 💥 Fully submersible Can be used underground A Halogen-free Gel Ø UV UV resistant Self-extinguishing and resistant

to abnormal heat and fire: Glow Wire Flammability Index at +960° C according to EN60695-2-12



FOX BOX

3 or 5 entrance jointing enclosure with gel filled perimeter chamber providing lighter weight with maximum capacity.

Kit includes accessories to maximise versatility allowing the use of cables from 8 to 18 mm in diameter or with 16, 20 and 32 mm diameter cable conduits. The internal, gel-free compartment allows for dry connections or any future alterations or disconnections. The gel, contained in the perimeter chamber also surrounds, insulates and seals any armour continuity connections or cable shields.

ADVANTAGES

- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- Functional, elegant design.
- Ideal for exposed and safety systems and for video camera installation.
- Ready for use.
- Click and hook closure, does not require screws.
- Ready and installable in all environmental conditions.
- Also suitable for wet or flooded environments.
- Always re-enterable.
- Wall or external ceiling fixing system.
- No shelf life.





